




TOP VIEW



FRONT VIEW



SIDE VIEW



PERSPECTIVE

SPECIFICATIONS:

EFFECTIVE FILTRATION AREA: 700 FT.

DESIGN FLOW RATE: 150 GPM.

FILTER TYPE: DUAL QUAD-CLUSTER POLYESTER CARTRIDGE.

FILTER TANK: INJECTION-MOLDED GLASS REINFORCED CO-POLYMER.

FILTER ELEMENTS: EIGHT REINFORCED POLYESTER CARTRIDGES.


PERFORMANCE RANGE: 1/2 TO 3 HP (30 TI 150 GPM) .37 TO 2.24 kW (114 TO 568 LPM).

MAXIMUM WORKING PRESSURE: 50 PSI.

TURNOVER 8 HOURS (GAL): 72 000.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5030-013.



HCF SERIES CARTRIDGE FILTERS

HCF SERIES CARTRIDGE FILTERS: HCF7030C